Variable Speed Drives and Soft Starters	Soft Starters	Altistart 22	**All-in-one Soft Starters for electrical motors from 4 to 400kW**

Features

Soft start/soft stop unit for infrastructure and industrial applications

Altistart 22 soft start/soft stop unit for 3-phase asynchronous motors

Simplifies installation and operation

- Saves time on wiring (6 terminals instead of 12)
- Optimises the size of your enclosures (very compact product)
- Keeps temperature rises to a minimum (low heat dissipation)
- Reduces the number of components to manage (multifunction product)

Protects your installations

- Minimises jolts and shocks
- Reduces mechanical stresses on the machines
- Increases the service life of your installations
- Prevents installation failure by detecting and signalling faults such as a blocked motor, underload or incorrect earthing of one of the 3 phases

A safe product with numerous integrated functions

- Bypass and safety functions
- Protection devices for monitoring the motor, the electrical installation and the starter itself
- Simple setup and operation with:
- 4 light emitting diodes (LEDs)
- 4 navigation keys
- 4-digit display
- [SoMove software](#) for configuring on PC and transferring the configuration via Bluetooth® or using a cable
- Coated cards as standard for enhanced resistance to harsh environments

Benefits

Bypass the stresses and let your applications take the strain

- Integrates bypass and safety functions

			• Reduces your operating costs • Simplifies wiring • Protects your electrical installation • Saves space with a fully equipped product Applications • Pumps • Fans • Compressors