

<p>Variable Speed Drives and Soft Starters</p>	<p>Soft Starters</p>	<p>Altistart 48</p>	<p><u>Soft Starters for heavy duty industry & pump from 4 to 900kW</u></p> <p>Features 230... 415 V / 208... 690 V - 50/60 Hz</p> <ul style="list-style-type: none"> • Starting and stopping of the machine by the Altistart 48 torque control system (TCS patent: Torque Control System) • Thermal protection of the motor • Protection of the machine: underload and overload with adjustable threshold and times, locked rotor, rotation direction control • Factory set for immediate start-up • Simplified customisation of settings using built-in display or the PowerSuite software • Through connection • Control of starter bypass contactor to prevent heat dissipation • Dual configuration (2 motors) • Numerous configurable inputs/outputs • Cascaded starting and deceleration of a number of motors • Modbus Integrated, FIPIO, PROFIBUS DP, DeviceNet, Ethernet <p>Benefits Taming energy Altistart 48 offers you the benefits of its patented Torque Control System (TCS). Ready for immediate start-up, with simplified wiring and extended communication functions, it can be integrated at the heart of your applications in complete simplicity.</p> <p>Applications</p> <ul style="list-style-type: none"> • Pumps • Fans and high inertia machines • Compressors • Conveyors
---	-----------------------------	----------------------------	--